


DETAIL B (5/1)
(SECTION A-A)



GENERAL TOLERANCE (HOUSING)									USED ON
10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VR	ANGLE	ST730365
±0.15	±0.20	±0.30	±0.40	±0.50	±0.75	±0.9	±1.4	±30°	ST730366

주 기

1. 재품가능상 유해한 BURR,변형 및 WELDLINE 등이 없을 것.
2. 적용 HOUSING : MG620057
3. 적용 TERMINAL : ST730365,366,431
4. 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬,PBBs,PPDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : MG620057
3. APPLICABLE TERMINAL : ST730365,366,431
4. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD MERCURY,CADMIUM, HEXAVALENT CHROMIUM,PPBBs,PPDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2017-08-10

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Terminal Co., Ltd.
Korea Electric Terminal Co., Ltd.

ISSUE MARK

KET KOREA ELECTRIC
TERMINAL CO., LTD.

				MATERIAL		NYLON 66		 KOREA ELECTRIC	
				FINISH		NATURAL		TERMINAL CO., LTD.	
				WTR RANGE		CLASS		7123 - 1210	
				INSULATION		TYPE		2FB - 12F	
 99-158 (2018.12.18)				MFG		76.09.23			
LFR		REVISION RECORD		DR		CHK		APP	
DR				CHK				PART NO.	
						±0.3		SOLDER 5/1	
								MG610058	
APP		J/WK - K		CHK		PART NAME		2.3 mm PLUG HOUSING 12P	
				APP: Watanabe					