

MG610088

PART NO.






CUSTOMER DRAWING

DIMENSIONS IN MM

GENERAL TOLERANCE (HOUSING)

USED ON

10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	



NO.	MATERIAL	COLOR
0	P B T:	NATURAL
1		RED
2		BLUE
3		YELLOW
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE

주 기

1.적용 TERMINAL: 7155-1591, 1592

2.CONNECTOR 이탈력 8Kgf 이상

NOTE

1.APPLICABLE TERMINAL :

7155-1591, 1592

2.CONNECTOR RETENTION FORCE :
OUT 8.0Kgf MIN

2008.02.13

ISSUE MARK

△ 설계사항변경(S060120)근거 수정 (형상변경-CHAMFER 설정)	LDG		'06.04.24
△ 설계사항변경(S050286)근거 수정	JYS		'05.12.12
△ 사양변경(S050178)근거 수정	CJH		'05.08.11
△ 사양변경(S040054)근거 수정	MKNQ		'04.05.10
△ 사양변경(980051)근거 수정	INO		'98.12.21

LTR	REVISION RECORD	DR	CHK	APP.	DATE
	WON. 97.04.07				

CHK.	R:\LIBRARY\2008\mg6-010088	APP.	R:\LIBRARY\2008\mg6-010088
------	----------------------------	------	----------------------------

MATERIAL	SEE TABLE
FINISH	SEE TABLE
WIRE RANGE	
INSULATION	

SCALE	2/1
-------	-----

PART NAME	TLC 3F HS'G
-----------	-------------

KET
ENGINEEREDKOREA ELECTRIC
TERMINAL CO., LTD.CLASS ϕ 1.0

TYPE 7119-6030

PART NO. MG610088