PART NO. MG610128T-*02

CUSTOMER DRAWING

(DIMENSIONS IN MM)

GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	50MAX	100MAX	100VR	( )	
±0.25	±0.35	±0.55	±0.95	±1.0	



PART NO. *표시는 색상 표기임.

	NO.	COLOR
*	0	NATURAL
	1	RED
	2	BLUE
	3	YELLOW
	4	GRAY
	5	BLACK
	6	GREEN

주 기

1.기능상 유해한 FLASH, BURR, WELDLINE 없을 것
2.지시하지 않은 모든 R은 0.3R.
3.적용 TERMINAL : ST730335-3, 730910-3
적용 HOUSING : MG620129T-*02
4.제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF FLASH, BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
3. APPLICABLE TERMINAL : ST730335-3, 730910-3
APPLICABLE HOUSING : MG620129T-*02
4. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXAVALENT CHROMIUM,PBBs,PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2019-11-05

KOREA ELECTRIC TERMINAL CO., LTD. Electronic Produc t Development Team

ISSUE MARK

LTR	REVISION RECORD	DR. / CHK.	APP.	DATE

DR. LYS '17.11.01	CHK. PSH '17.11.01
CHK. KSH '17.11.01	APP. BUC '17.11.01

MATERIAL	PET+PC(GWIT)	KET ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	
INSULATION		TYPE	
TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE 2/1	PART NO. MG610128T-*02
PART NAME	1006P - 02		