



NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8		GREEN

GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.10	

주 기

- 1.기능상 유해한 BURR 및 WELDLINE 등이 없을것.
- 2.착용 TERMINAL: ST730497, ST730498
- 3.착용 HOUSING: MG621518
- 4.착용 REAR HOLDER: MG631519
- 5.CONNECTOR 삽입력 & 발거력: 9.0Kg이하

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL :ST730497, 730498
2. APPLICABLE HOUSING :MG621518
2. APPLICABLE REAR HOLDER :MG631519
6. CONNECTOR RETENTION FORCE : IN 9.0Kgf MAX OUT 5.0Kgf MAX



ISSUE MARK

				MATERIAL SEE NOTE		KET KOREA ELECTRIC (ENGINEERED) TERMINAL CO., LTD.						
				FINISH NATURAL								
				WIRE RANGE		CLASS .070 II						
				INSULATION		TYPE						
△ 시험완료(98.03.02)본격 수검		I/O		'99.02.10								
LTR	REVISION RECORD			DR	CHK	APP	DATE	PREPARED AS NOTE	SEE TABLE	SCALE 1/1	PART NO.	MG611517
CHK	JANG 98.03.23			CHK		98.03.23		PART NAME				
DR	98.03.25			APP		98.03.25		SDLI 20P PLUG HOUSING				