



GENERAL TOLERANCE (HOUSING)								USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT		
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1		

주 기

1.지시없는 C, R은 0.5로 할 것.

2.기능상 유해한 BURR,변형,WELDLINE등이 없을 것.



3.상대 적용 HOUSING : MG641234

4.적용 REAR HOLDER : MG631233

5.적용 TERMINAL : ST740709

6.적용 CLIP : MG630418(ø7.0 SDL, SWP CLIP)

△ 7.제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.



△ DETAIL "B"
(S= 5/1)

NOTE

1.UNLESS OTHERWISE SPECIFIED ALL RADIUS

TO BE 0.5 RADIUS.

UNLESS OTHERWISE SPECIFIED ALL CHAMFERS

TO BE 0.5 CHAMFER.

2.MUST BE FREE OF FLASH, WELDLINE

AND IMPERFECTION THAT AFFECT FUNCTION.

3.APPLICABLE HOUSING : MG641234

4.APPLICABLE REAR HOLDER : MG631233

5.APPLICABLE TERMINAL : ST740709

6.APPLICABLE CLIP : MG630418 (ø7.0 SDL, SWP CLIP)

△ 7.6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY,

CADIUM,HEXAVALENT CHROMIUM,PBBs,PBDEs) SHALL

NOT EXCEED THE MAXIMUM PERMISSIBLE

CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE

& RoHS REGULATION.

ISSUE MARK

				MATERIAL  PBT		 KOREA ELECTRIC	
				FINISH BLACK		TERMINAL CO., LTD.	
				WIRE RANGE		CLASS	
				INSULATION		TYPE Y7182-8730-30	
				TOLERANCE SEE TABLE		PART NO. MG611611-5	
				SCALE 2/1			
				PART NAME			