




PART NO. SEE TABLE

CUSTOMER DRAWING

PART NO.	PART NAME	MATERIAL	COLOR	오삽입방지를 LIB위치	GENERAL TOLERANCE (HOUSING)					USED ON
MG611809	DOOR 18F HS'G (L)	PBT	NATURAL	"A"	10MAX	20MAX	45MAX	ANGLE	ECCENT	
MG611810-4	DOOR 18F HS'G (R)	PBT	LIGHT GRAY	"B"	±0.2	±0.25	±0.3	±30'	0.10	



SECTION A-A




DETAIL "C"
(S=2/1)

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을것.
2. 적용 TERMINAL: ST730675, 676, 677
3. 적용 HOUSING: MG621807
4. 적용 SPACER: MG631811-9

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL :ST730675, 676, 677
3. APPLICABLE HOUSING :MG621807
4. APPLICABLE SPACER :MG631811-9



ISSUE MARK

		MATERIAL SEE TABLE		Korea Electric	
		FINISH SEE TABLE		TERMINAL CO., LTD.	
△ 사방머리(5000106)까지 보면 색차지 (LOOK COLOR WITH IN LOOK LEADER WITH COLOR)		KDJ	06.05.15	WIRE RANGE CLASS .090 II	
△ 사방머리(5000106)까지-꼭감압까지		ING	99.06.30	INSULATION TYPE	
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE
DR.	INO '99.02.10.	CHK			2/12
CHK		APP.			2/12
		SCALE 1/1		PART NO. SEE TABLE	
		PART NAME		DOOR 18F HS'G (L), (R)	

(DIMENSIONS IN MM)