



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL: ST730775, 776, 777  
APPLICABLE HOUSING: MG622232, MG641053  
APPLICABLE SPACER: MG632233
- △ 3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.



주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
2. 적용 TERMINAL: ST730775, 776, 777  
적용 HOUSING: MG622232, MG641053  
적용 SPACER: MG632233
- △ 3. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.



ISSUE MARK

		MATERIAL		PBT		KOREA ELECTRIC TERMINAL CO., LTD.	
		FINISH		NATURAL			
		WIRE RANGE		CLASS		.090	
△ 3. 유해물질(납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.		DR.	CHK.	APP.	DATE	INSULATION TYPE	TYPE
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	INSULATION TYPE	TYPE
DR.	WON. 2000.9.07	CHK.	CHK.	APP.	DATE	SEE TABLE	SIGLE 2/1
CHK.		CHK.	CHK.	APP.	DATE	PART NO. MG612243	
PART NAME						ASC 15F HOUSING	