



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

NOTE

- MUST BE FREE OF BURR, WEIDLIN AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL: ST730775, 776, 777
APPLICABLE HOUSING: MG622232, MG641053
APPLICABLE SPACER: MG632233
- ⚠ 3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL: ST730775, 776, 777
적용 HOUSING: MG622232, MG641053
적용 SPACER: MG632233
- ⚠ 3. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안 된다.

APPROVED

2018-12-07

**KOREA ELECTRIC
TERMINAL CO., LTD.
Product Development
Team 1**

ISSUE MARK

		MATERIAL		PBT		KOREA ELECTRIC TERMINAL CO., LTD.			
		FINISH		NATURAL					
		WIRE RANGE		CLASS		.090			
		INSULATION		TYPE					
⚠ 설계사양변경(S090174) 근거 도면제작상 (SPACER 입수부 "R" 추가)		BJG		'09.07.06					
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.	
	WON. 2000.9.07					SEE TABLE	2/1	MG612243	
CHK.		APP.						PART NAME	ASC 15F HOUSING