



GENERAL TOLERANCE (HOUSING)

10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	USED ON
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
 2. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
 3. APPLICABLE PART : TERMINAL-ST730924/ST730925 R/HOLDER-MG632606
 4. COMPARE HOUSING-MG642602
- 주 기**
1. 지시없는 R는 전부 0.3으로 한다.
 2. 기능상 유해한 BURR, 변형등이 없을것.
 3. 적용 부품 : TERMINAL - ST730924 / ST730925 R/HOLDER-MG632606
 4. 적용 HOUSING - MG642602



ISSUE MARK

						MATERIAL	PBT	 KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH	BROWN		
						WIRE RANGE			CLASS 91RK (040 WP)
						INSULATION			TYPE 7183-7771-80
LTR	REVISION RECORD		DR	CHK	APP	DATE	TERMINAL EXCEPT AS NOTED	SCALE	PART NO.
	DR. HEO. 03. 05. 21			CHK		05.24	SEE TABLE	2/1	MG612603
CHK.			APP	CHK		05.24	PART NAME	RK 3P PLUG HS'G (RK03FBR)	