



GENERAL TOLERANCE (HOUSING)				USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT
±0.2	±0.25	±0.3	±30'	0.1

1. MUST BE FREE OF BURR, WELDLINE

AND IMPERFECTION THAT AFFECT FUNCTION

2. APPLICABLE HOUSING : MG622724T/MG622880T

TERMINAL : ST730872-3/694-3/695-3/696-3/697-3

REAR HOLDER : MG631168-3

3. 6HAZARDOUS SUBSTANCES IN PARTS (Lead, Mercury,

Cadmium, Hexavalent Chromium, PBBs, PBDEs) SHALL NOT

EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED

UNDER EU ELV DIRECTIVE & ROHS REGULATION

ISSUE MARK

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
2. 적용 하우징 : MG622724T/MG622880T
터미널 : ST730872-3/694-3/695-3/696-3/697-3
리플더 : MG631168-3
3. 제품 내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용농도를 초과해서는 안 된다.

주 기

					MATERIAL	PE1+PC (GWIT)	 KIEP KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.
					FINISH	NATURAL	
					WIRE RANGE	CLASS	
					INSULATION	TYPE	
						1806 D/L	
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE		
DR.	PJM '12.02.28	CHK.	2/18	2/28			
CHK.		APP.	2/28		PART NAME	SCALE	PART NO.
					1806DL 9F HSG_GWIT	2/1	MG612725T