







GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	



SECTION A-A

주 기

- 기능상 유해한 BURR 및 미성형이 없을것.
- 상대 HOUSING PART NO. : MG642874 (CONN ASSY-CONTACT FEMALE)
- 적용 TERMINAL: ST730775, 776, 777 (ASC TYPE)  
ST730916, 921, 922, 923 (.250 TYPE)
- 적용 HOLDER: MG632920



ISSUE MARK

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING : MG642874 (CONN ASSY-CONTACT FEMALE)
- APPLICABLE TERMINAL : ST730775, 776, 777 (ASC TYPE)  
ST730916, 921, 922, 923 (.250 TYPE)
- APPLICABLE HOLDER : MG632920

						MATERIAL PBT		KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH NATURAL			
						WIRE RANGE		CLASS	
						INSULATION		TYPE	
LTR	REVISION RECORD	DR	CHK	APP.	DATE	TERMINAL RANGE IN SERIES	SCALE	PART NO.	
DR.	KYM 04. 01. 13	CHK	[Signature]	APP.	01/13	SEE TABLE	2/1	MG612919	
CHK.		APP.	[Signature]		01/13	PART NAME	2509 5F HS'G		