





GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 지시하지 않은 반경 R은 0.3로 한다
2. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
3. 적용 HOUSING : MG643094
- 적용 R/HOLDER : MG633098
- 적용 TERMINAL : ST730924/ST730925

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADII TO BE 0.3 RADIUS.
2. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE HOUSING : MG643094
- APPLICABLE R/HOLDER : MG633098
- APPLICABLE TERMINAL : ST730924/ST730925



ISSUE MARK

				MATERIAL	PBT	 KET KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	GRAY	
				WIRE RANGE		CLASS 91RK (040 WP)
				INSULATION		TYPE 7183-7775-40
REVISION RECORD				DR	CHK	PART NO. MG613097
DR. HE0 S.H 04. 1. 16				CHK	APP.	
CHK. 01.19				APP.	01.19	
				PART NAME		RK 8P PLUG HS*G (RK08FGY)