



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : ST730948-3/993-3
APPLICABLE R/HOLDER : MG633659-1
- 6HAZARDOUS SUBSTANCES IN PARTS (Lead, Mercury, Cadmium, Hexavalent Chromium, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION

NO.	MATERIAL	COLOR
0	PBT (V0)	NATURAL
1		RED
2		BLUE
3		YELLOW
5		BLACK

주 기

- 기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 적용 터미널 : ST730948-3/993-3
적용 R/HOLDER : MG633659-1
- 제품 내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용농도를 초과해서는 안 된다.

ISSUE MARK	
------------	--

					MATERIAL PBT(V0)		KIET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.
					FINISH NATURAL		
3	설계사양변경(S110128)근거 도면 제작성	PJM			'11.04.28	WIRE RANGE	CLASS
2	설계사양변경(S090047)근거 도면 제작성	CJH			'09.03.25	INSULATION	TYPE 250 DOOR LOCK
1	설계사양변경(S060011)근거 도면 제작성	JJY			'06.01.16	TOLERANCE EXCEPT AS NOTED SEE TABLE	PART NO. MG613356
LTR	REVISION RECORD		DR.	CHK.	APP.	DATE	SCALE 2/1
DR. HAK. '04.07.16		CHK.				PART NAME	250 3F HOUSING
CHK. 8/16		APP. 8/16					