



SECTION A-A

GENERAL TOLERANCE (HOUSING)								USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT		
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1		

NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
- UNLESS OTHERWISE SPECIFIED ALL CHAMFERS TO BE 0.3 CHAMFER.
- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : 730675, 676, 677
- KET MARK : TAPER 15° (H; 0.1~0.2, SIZE: 1.5) CAVITY NO. : TAPER 0°(H; 0.1~0.2, SIZE: 1.5)

주 기

- 지시하지 않은 반경 R은 0.3으로 한다.
- 지시하지 않은 모따기 C는 0.3으로 한다.
- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL : 730675, 676, 677
- KET 문자 : 기울기 15°(H; 0.1~0.2, SIZE: 1.5) CAVITY NO.: 기울기 0°(H; 0.1~0.2, SIZE: 1.5)



ISSUE MARK

				MATERIAL	PBT	KET (KOREA ELECTRIC TERMINAL CO., LTD.)	CLASS	090II
				FINISH	NATURAL			
				WIRE RANGE		TYPE	PART NO.	MG613806
				INSULATION				
LTR	REVISION RECORD			DR	CHK	APP.	DATE	THROWING DEFECT OR NOTES
DR.	H.E.M	'07.04.16	CHK.					
CHK.			APP.				PART NAME	090II 4F HOUSING (SINGLE LOCK)