



GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL  
090II : ST730675, 730676, 730677, 731100  
187II : ST730644, 730645, 730646
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL  
090II : ST730675, 730676, 730677, 731100  
187II : ST730644, 730645, 730646
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안 된다.



ISSUE MARK

						MATERIAL	PBT	KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH	NATURAL		
						WIRE RANGE	CLASS 1809		
						INSULATION	TYPE HYBRID		
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE 2/1	PART NO. MG614492
		DR.	H.S.KIM	'08.9.08	CHK.				
		CHK.			APP.				
							PART NAME	HYBRID 1809 4F HOUSING	