



GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NOTE

- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL :
 TYCO 150 964261,964263 (MT2)
 TYCO 950 962932 (MPT)
 TYCO 280 964280,964284,965999 (JPT)
- APPLICABLE TPA : MG634616-4
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.



ISSUE MARK

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL : TYCO 150 964261,964263 (MT2)
 TYCO 950 962932 (MPT)
 TYCO 280 964280,964284,965999 (JPT)
- 적용 TPA : MG634616-4
- 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

				MATERIAL PBT-GF30		KET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
				FINISH BLACK			
ECO NO.(1108-116) 근거 도면 제작성		LDG	-	25.AUG.'11	WIRE RANGE		CLASS Body-IP 68P
설계시양변경(110118) 근거 도면 제작성		LDG	-	19.APR.'11	INSULATION		TYPE
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED SEE TABLE	SCALE 1/1
DR.	BJG. 08.SEP.2010	CHK.	공기	APP.	08.SEP.'10	PART NAME	
CHK.		APP.	공기	APP.	08.SEP.'10	Body-IP 68F Housing	