






GENERAL TOLERANCE (HOUSING)						USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1

주 기

- 1.기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 2.적용 TERMINAL : ST731371-3,731372-3
- 적용 HOUSING : MG625430-5
- 적용 R/HOLDER : MG635611-1
- 3.제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- 1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- 2. APPLICABLE TERMINAL : ST731371-3,731372-3
- APPLICABLE HOUSING : MG625430-5
- APPLICABLE R/HOLDER : MG635611-1
- 3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXVALENT CHROMIUM,PBBs,PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.



REFERENCE

(DIMENSIONS IN MM)

						MATERIAL	PBT
						FINISH	BLACK
						WIRE RANGE	CLASS 110(WP)
						INSULATION	TYPE
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE
DR.	KSH '2012.10.26	CHK.				SEE TABLE	2/1
CHK.		APP.	BUC '12.10.29			PART NAME	110(WP) 7F HOUSING

ISSUE MARK

KET KOREA ELECTRIC
TERMINAL CO., LTD.