


PART NO. MG620033	GENERAL TOLERANCE (HOUSING)							USED ON
	10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	
CUSTOMER DRAWING								
	NOTE 1. MUST BE FREE OF FLASH, SINK,WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION. 2. APPLICABLE TERMINAL : ST750293-3, 750294-3 3. APPLICABLE HOUSING : MG610034 4. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXAVALENT CHROMIUM,PBBs,PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.							
	ISSUE MARK							
					MATERIAL	NYLON	 KOREA ELECTRIC TERMINAL CO., LTD.	
					FINISH	NATURAL		
					WIRE RANGE		CLASS	
△2	설계사양변경(S110128)근거 도면 재작성			'11.04.28	INSULATION		TYPE	
△1	명칭 변경(전Ø1.3 PIN 12P HSG)			'85.11.28	TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE	PART NO.
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE		1/1	MG620033
DR.	85 9/15	CHK.				PART NAME		
CHK.	J. w	APP.				△1 Ø1.3 REC HOUSING 12P		