

PART NO.

MG620081

CUSTOMER DRAWING

DIMENSIONS IN MM

GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

36.0

18.60

22.60

19.60

22.40

25.80

12.20

NO.	MATERIAL	COLOR
0	NYLON	NATURAL
1		RED
2		BLUE
3		YELLOW
5		BLACK

주 기

1.기능상 유해한 BURR, WELDLINE 없을 것

2.적용 TERMINAL: ST750207,208,330

3.제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.

2. APPLICABLE TERMINAL : ST750207,208,330

3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXAVALENT CHROMIUM,PBBs,PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

ISSUE MARK

MATERIAL

NYLON

FINISH

SEE TABLE

WIRE RANGE

CLASS

INSULATION

TYPE

TOLERANCE EXCEPT AS NOTED

SEE TABLE

SCALE

1/1

PART NAME

ø2.0 REC HOUSING 12P (DOUBLE LOCK)

설계사양변경(S110128)근거 도면 재작성

KSJ

'11.04.27

LTR

REVISION RECORD

DR.

CHK.

APP.

DATE

DR.

87.09.28

CHK.

87.09.29

CHK.

J. wkw

APP.

W. wkw

MG620081

MG620081