



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

주 기

- 기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 적용 TERMINAL : ST740634, 635, 637, 682
- 적용 HOUSING : MG610981
- 적용 REAR HOLDER : MG630989
- 제품 내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬 PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용농도를 초과해서는 안 된다.

NOTE

- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : ST740634, 635, 637, 682
- APPLICABLE HOUSING : MG610981
- APPLICABLE REAR HOLDER : MG630989
- 6HAZARDOUS SUBSTANCES IN PARTS (Lead, Mercury, Cadmium, Hexavalent Chromium, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION

ISSUE MARK

					MATERIAL	PBT(V0)	KIET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
					FINISH	NATLURAL		
					WIRE RANGE		CLASS	
					INSULATION		TYPE	
△	설계사양변경"SI10128"근거 도면 재작성	DR.	CHK.	APP.	DATE	'11.04.28		
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED SEE TABLE	SCALE 2/1	PART NO. MG 620982
	DR. KO 95.10.09	CHK. Sik			95.10.09	PART NAME	3220 (EDL)-1P REC HS'G	
	CHK. 12/26	APP. 12/27						