






GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	



**NOTE**

- 1.기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 2.적용 TERMINAL : ST740672-3,673-3,674-3(090 II)
- 적용 PLUG HOUSING : MG611809(L),MG611810-41(R)
- 적용 SPACER : MG631808-3(2EA)



ISSUE MARK

**NOTE**

- 2.MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- 3.APPLICABLE TERMINAL: ST740672-3,673-3,674-3(090 II)
- APPLICABLE PLUG HOUSING:MG611809(L),MG611810-41(R)
- APPLICABLE SPACER : MG631808-3(2EA)

△	소재시험변경(S060028)근거 도면 제작명	DR	06.01.20	MATERIAL	PBT	KOREA ELECTRIC TERMINAL CO., LTD.
△	시험변경(050143)근거-형상변경	DESIGN	05.06.13	FINISH	NATURAL	
△	시험변경(990128)근거-형상변경	CHK	99.07.20	WIRE RANGE		CLASS
△	시험변경(990105)근거-색상일치	APP	99.06.30	INSULATION		TYPE
LTR	REVISION RECORD	DR	DATE	ISSUANCE DATE	SEE TABLE	SCALE
DR	MAN 99.02.03.	CHK	2/3	1/1		PART NO.
CHK	2/3	APP	2/4			MG621807
						PART NAME
						DOOR 36P REC HS'G