







SECTION A-A



SECTION B-B



GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL: ST740672, 673, 674
 APPLICABLE HOUSING: MG612254, MG651086
 APPLICABLE SPACER: MG632257
 APPLICABLE CLIP: MG631267, 631268, 631471, 632019

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
2. 적용 TERMINAL: ST740672, 673, 674
 적용 HOUSING: MG612254, MG651086
 적용 SPACER: MG632257
 적용 CLIP: MG631267, 631268, 631471, 632019



ISSUE MARK

		MATERIAL		PBT		KOREA ELECTRIC	
		FINISH		NATURAL		TERMINAL CO., LTD.	
△	사명변경(050093)내기 도면 변경	DR/CHK	2005.04.20	WIRE RANGE	CLASS .090		
△	CLIP 및 도면 수정	DR/CHK	2002.12.10	INSULATION	TYPE		
LTR	REVISION RECORD	DR	APP.	DATE	SEE TABLE	SCALE	PART NO.
DR	WON. 2001.08.22	CHK		5/04		1/1	MG622256
CHK		APP.	5/04		PART NAME		ASC 22M HOUSING