



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.

2. 적용 TERMINAL: ST740672, 673, 674

적용 HOUSING: MG612034, MG651032

적용 SPACER: MG632036

적용 CLIP: MG631267, 631268, 631471, 632019

△ 3. 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬,PBBs,PBDEs)은 EU,

ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF BURR, WELDLINE

AND IMPERFECTION THAT AFFECT FUNCTION.

2. APPLICABLE TERMINAL :ST740672, 673, 674

APPLICABLE HOUSING :MG612034, MG651032

APPLICABLE SPACER :MG632036

APPLICABLE CLIP :MG631267, 631268, 631471, 632019

△ 3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, NOT CADMIUM, PBBs, PBDEs, HEXAVALENT CHROMIUM)

SHALL EXCEED THE MAXIMUM PERMISSIBLE

CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.



				MATERIAL		PBT	
				FINISH		NATURAL	
				WIRE RANGE			
				INSULATION			
LTR		REVISION RECORD		DATE		SCALE	
DR.		WON. 2003.01.10		CHK		2/1	
CHK.				APP.		PART NAME	
				1/15		ASC 3M HOUSING (NEW)	
				1/15			

**KET** KOREA ELECTRIC TERMINAL CO., LTD.

CLASS ASC

TYPE

PART NO. MG622938