

PART NO

MG631228, 633990

CUSTOMER DRAWING

(DIMENSIONS IN MM)

GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

5.40

3.20

14.00

15.60

9.00

0.80

1.00

0.70

D

E

0.80

1.60

2.80

1.80

K E T 1

NO.	PART NO.	D	E	FINISH
1	MG631228	10.10	6.40	YELLOW
△1	MG633990	9.30	5.70	BLACK

주 기

1.기능상 유해한 FLASH, SINK,WELDLINE 등이 없을것.

2.적용 HOUSING:MG611227-3, 611225

MG611226-2, 612540-1

3.내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서

지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF FLASH, SINK,WELDLINE

AND IMPERFECTION THAT AFFECT FUNCTION.

2. APPLICABLE HOUSING : MG611227-3, 611225

MG611226-2, 612540-1

3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXAVALENT CHROMIUM,PBBs,PBDEs) SHALL

NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION

PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2016-03-07

KOREA ELECTRIC
TERMINAL CO., LTD.
Electronic Product Development Team

ISSUE MARK

					MATERIAL	NYLON66	KET ENGINEERED KOREA ELECTRIC TERMINAL CO., LTD.	
					FINISH	SEE TABLE		
					WIRE RANGE		CLASS	0709
△2	설계사양변경S110128근거 도면 재작성	PJM	KSH	02\sig\1772.bmp	'11.04.28	INSULATION	TYPE	MULTI
△1	설계사양변경(S070155)의거 도면재작성	KSH		10\SDA\1772.jpg	'07.07.04		PART NO.	MG631228, 633990
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	2/1
DR.	KO . '99. 7.29	CHK.			11/26	SEE TABLE		
CHK.		APP.			11/26	PART NAME		
						MULTI 1P REAR HOLDER		