



GENERAL TOLERANCE (HOUSING)

10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1

USED ON

주 기

1. 지시없는 R는 전부0.3으로 한다.
2. 기능상 유해한 BURR,변형등이 없을것.
3. 적용 HOUSING : MG613214 (Y7183-7870-80)

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
2. MUST BE FREE OF BURR,WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE HOUSING : MG613214 (Y7183-7870-80)



ISSUE MARK

							MATERIAL	PBT	KET ENGINEERED	KOREA ELECTRIC	
							FINISH	NATURAL		TERMINAL CO., LTD.	
							WIRE RANGE			CLASS	91RK (040 WP)
							INSULATION			TYPE	7158-4890
LTR	REVISION RECORD			DR	CHK	APP	DATE	SCALE		PART NO.	
DR	HEO S.H 04.8.13			CHK				SEE TABLE	5/1	MG633215	
CHK	8/23			APP		8/23	PART NAME				
							RK 2P FEMALE HS'G FRONT HOLDER(RK02FBR)				