

Technical drawing of a KET 1 MG634870 connector, showing multiple views with dimensions:

- Top View:** Dimensions include 1.90, 1.70, 4.20, 3.75, and 2-0.70.
- Front View:** Dimensions include 6.00 ±0.1 and 3.75.
- Side View:** Dimensions include 6.80, 15.60, 10.70, and 1.35.
- Bottom View:** Dimensions include 3.75.

The drawing also includes the text "KET 1" and "MG634870" on the front view.



1. MUST BE FREE OF BURR, WELDLINE
AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST731079-3
3. 6HAZARDOUS SUBSTANCES IN PARTS (Lead,
Mercury, Cadmium, Hexavalent Chromium, PBBs,
PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE
CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE
& RoHS REGULATION

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을것.
2. 적용 터미널 : ST731079-3
3. 제품 내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬 PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용농도를 초과해서는 안 된다.

						MATERIAL PA66 (V0)		 KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH ⚠ SEE TABLE			
						WIRE RANGE			CLASS .187
						INSULATION			TYPE P-LOCK
⚠	ECO-1512-180의거 도면 재작성	SMG	KSH	BUC	'15.12.09				
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE 2/1	PART NO. MG635263
DR.	LCM 2010.04.30	CHK.				PART NAME			
CHK.	KSH 2010.04.30	APP. BUC 2010.04.30				187 P-LOCK FLAG 2F HSG(HINGE)			