

Technical drawing of a KET 1 MG635263 connector, showing three views with dimensions in millimeters:

- Front View (Top Left):** Shows the connector's profile. Dimensions include a total width of 1.90, a central pin diameter of 1.70, a pin length of 4.20, and a mounting hole diameter of 3.75. The text "KET 1" and "MG635263" is visible on the side.
- Side View (Bottom Left):** Shows the connector's side profile. Dimensions include a total width of 6.80, a mounting hole diameter of 3.75, a central pin diameter of 1.70, a pin length of 4.20, and a mounting hole diameter of 3.75. The text "KET 1" and "MG635263" is visible on the side.
- Cross-sectional View (Right):** Shows the internal structure of the connector. Dimensions include a total width of 6.00, a central pin diameter of 1.70, a pin length of 4.20, and a mounting hole diameter of 3.75.



1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST731079-3
3. 6HAZARDOUS SUBSTANCES IN PARTS (Lead, Mercury, Cadmium, Hexavalent Chromium, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION

- 1.기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 2.적용 터미널 : ST731079-3
- 3.제품 내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬 PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용농도를 초과해서는 안 된다.

					MATERIAL PA66 (VO)		 KOREA ELECTRIC TERMINAL CO., LTD.
	ECO-1902-222의거 도면 재작성	YHJ / KSH	KHG	'19.02.21	FINISH  SEE TABLE		
	ECO-1809-184의거 도면 재작성	YHJ / KSH	BUC	'18.09.14	WIRE RANGE		CLASS .187
	ECO-1801-117의거 도면 재작성	LYS / KSH	BUC	'18.01.08	INSULATION		
	ECO-1512-180의거 도면 재작성	SMG / KSH	BUC	'15.12.09	TYPE		P-Lock
LTR	REVISION RECORD	DR. / CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED SEE TABLE	SCALE 2/1	PART NO. MG635263
DR.	LCM 2010.04.30	CHK.					
CHK.	KSH 2010.04.30	APP.	BUC 2010.04.30	PART NAME 187 P-Lock FLAG 2F HSG(HINGE)			