





PART NO. MG635389

CUSTOMER DRAWING




GENERAL TOLERANCE (HOUSING)

10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT
±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1

USED ON

주 기

- 지시하지 않은 반경 R은 0.3으로 한다.
- 지시하지 않은 모따기 C는 0.3으로 한다.
- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- CLIP HOUSING 삽입력 : 6 kgf 이하
이탈력 : 11 kgf 이상
- 적용 HOUSING : MG620153, MG620053, MG620055
MG620057, MG620122, MG620072
- KET 문자 : 기울기 15°(H; 0.1~0.2, SIZE: 1.5)
PART & CAVITY NO.: 기울기 0°(H; 0.1~0.2, SIZE: 1.5)
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.



NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADIUS
TO BE 0.3 RADIUS.
- UNLESS OTHERWISE SPECIFIED ALL CHAMFERS
TO BE 0.3 CHAMFER.
- MUST BE FREE OF BURR, WELDLINE
AND IMPERFECTION THAT AFFECT FUNCTION.
- CLIP HOUSING INSERTION FORCE : 6 kgf MAX
RENTENTION FORCE : 11 kgf MIN
- APPLICABLE HOUSING :MG620153, MG620053, MG620055
MG620057, MG620122, MG620072
- KET MARK : TAPER 15° (H; 0.1~0.2, SIZE: 1.5)
PART & CAVITY NO. : TAPER 0°(H; 0.1~0.2, SIZE: 1.5)
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY,
CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL
NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION
PRESCRIBED UNDER EU ELV DIRECTIVE

NO.	MATERIAL	COLOR
0	PA66	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
* 5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE

ISSUE MARK

						MATERIAL	SEE TABLE		
						FINISH	SEE TABLE		
						WIRE RANGE	CLASS	090	
						INSULATION	TYPE	090 CLIP	
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.	
DR.	KYJ	2011.02.17	CHK.			SEE TABLE	2/1	MG635389-5	
CHK.			APP.			PART NAME	090 CLIP (ø7.0 KEY HOLE TYPE)		

(DIMENSIONS IN MM)

 KET KOREA ELECTRIC
TERMINAL CO., LTD.