



SECTION A-A

GENERAL TOLERANCE (HOUSING)

10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	USED ON
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

*

NO.	MATERIAL	COLOR
0	PA66	NATURAL
1		RED
2		BLUE
3		YELLOW
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11	ORANGE	

주기

- 1, 지시하지 않은 반경 R은 0.3로 한다,
- 2, 지시하지 않은 모따기 C는 0.3으로 한다,
- 3, 기능상 유해한 BURR 및 WELDLINE 등이 없을 것,
- 4, 적용 HOUSING: N060,09011 MALE HOUSING
- 5, 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다,

NOTE

- 1, UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS,
- 2, UNLESS OTHERWISE SPECIFIED ALL CHAMFERS TO BE 0.3 CHAMFER,
- 3, MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION,
- 4, APPLICABLE HOUSING: N060,09011 MALE HOUSING
- 5, 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION,

APPROVED

2019-11-05

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

					MATERIAL	SEE TABLE	KET ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.
					FINISH	SEE TABLE		
					WIRE RANGE	CLASS		
					INSULATION		TYPE	
⚠	검사성적서 합격에 따른 도면 재작성	JJH	CKY	SUK	16/10/07			
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
	YTK 2016.06.21		CHK, CKI		2016.06.21	SEE TABLE	2/1	MG635786
CHK,			APP,	BIN	2016.06.21	PART_NAME	7 Pi KEY HOLE CLIP (10mm offset)	