





NO.	MATERIAL	COLOR
0	P P	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
* 5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE



ISO VIEW



NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.5 RADIUS.
2. UNLESS OTHERWISE SPECIFIED ALL CHAMFERS TO BE 0.5 CHAMFER.
3. MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
4. APPLICABLE MALE ASSY; MG646002
5. KET MARK ; TAPER 15° (H; 0.1~0.2, SIZE; 3.5)
6. CAVITY NO. ; TAPER 0° (H; 0.1~0.2, SIZE; 3.5)
7. HOUSING ETCHING SPEC ; KDP-6A
7. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.


GENERAL TOLERANCE (HOUSING)

10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1

USED ON

주 기

1. 지시하지 않은 반경 R은 0.5로 한다.
2. 지시하지 않은 모따기 C는 0.5으로 한다.
3. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
4. 적용 MALE ASSY; MG646002
5. KET 문자 ; 기울기 15° (H; 0.1~0.2, SIZE; 3.5)
6. CAVITY NO. ; 기울기 0° (H; 0.1~0.2, SIZE; 3.5)
7. HOUSING 표면 부식 사양; KDP-6A
7. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.



APPROVED

2019-11-06

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

				MATERIAL	SEE TABLE	KET ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE		
				WIRE RANGE	-	CLASS	-
				INSULATION	-	TYPE	025/060/110
				TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE 1/1	PART NO. MG635812-5
				PART_NAME	REAR DOOR 22M WIRE COVER (STRAIGHT TYPE)		

				CHK, LIM, SUX	17.06.22
				DR, CHK, APP, DATE	
				DR, NST 2016.11.21	CHK, LJE 2016.11.21
				CHK,	APP, BIN 2016.11.21