








NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
* 5		BLACK
6		GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE



NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.

2. UNLESS OTHERWISE SPECIFIED ALL CHAMFERS TO BE 0.3 CHAMFER.

3. MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.

4. APPLICABLE HOUSING: MG656907

5. KEY MARK : TAPER 15° (H: 0.1~0.2, SIZE: 2.0)
CAVITY NO. : TAPER 0° (H: 0.1~0.2, SIZE: 2.0)

6. HOUSING ETCHING SPEC : KDP-6A

7. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PPDEs) SHOULD NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

				MATERIAL	SEE TABLE	 KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE	
				WIRE RANGE	-	
				INSULATION	-	CLASS HYBRID
				TOLERANCE EXCEPT AS NOTED	SCALE 1/1	TYPE 02510601110/250/FAKRA
				PART_NO.	MG635821	
				PART_NAME	025060110250 FAKRA 54F LEVER	

APPROVED

2019-11-05

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

GENERAL TOLERANCE (HOUSING)										USED ON
10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30°	0.1	

주 기

1. 지시하지 않은 반경 R은 0.3로 한다.

2. 지시하지 않은 모파기 C는 0.3으로 한다.

3. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.

4. 적용 HOUSING: MG656907

5. KET 문자 : 기울기 15° (H: 0.1~0.2, SIZE: 2.0)
CAVITY NO. : 기울기 0° (H: 0.1~0.2, SIZE: 2.0)

6. HOUSING 표면 부식사양 : KDP-6A

7. 제품내 함유된 6대 유해물질(납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.