





ISO VIEW
SCALE 1/2



GENERAL TOLERANCE (HOUSING)										USED ON
10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	


NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
2. UNLESS OTHERWISE SPECIFIED ALL CHAMFERS TO BE 0.3 CHAMFER.
3. MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
4. APPLICABLE FEMALE ASSY: MG644145
APPLICABLE CORRUGATED TUBE : $\varnothing 5.0$
5. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHOULD NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

주기

1. 지시하지 않은 반경 R은 0.3로 한다.
2. 지시하지 않은 모따기 C는 0.3으로 한다.
3. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
4. 적용 FEMALE ASSY: MG644145
적용 CORRUGATED : Ø5.0
5. 제품내 함유된 6대 유해물질(납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NO.	MATERIAL	COLOR
0	PP	NATURAL
1		RED
11		ORANGE
2		BLUE
22		JADE
3		YELLOW
4		GRAY
41		LIGHT GRAY
42		DARK GRAY
5		BLACK
61		LIGHT GREEN
62		DARK GREEN
7		BROWN
9		MAGENTA



					MATERIAL	SEE TABLE	 KOREA ELECTRIC TERMINAL CO., LTD. 2019-11-05 KOREA ELECTRIC TERMINAL CO., LTD. Korea Electric To W. H Co., LTD.
					FINISH	SEE TABLE	
					WIRE RANGE	—	CLASS 040
					INSULATION	—	TYPE —
 경보 합격에 의한 양산도면 출 LTR REVISION RECORD DR. LJJ 2017.09.06 CHK.	LJJ DR.	A/JH CHK.	CMS APP.	18.01.08 DATE	TOLERANCE EXCEPT AS NOTED SEE TABLE	SCALE 1/1	PART NO. MG635854
CHK.	APP. SSH 2017.09.06		PART_NAME 040 WP 4F WIRE COVER				