



SEC A-A



주 기

1. 지시하지 않은 반경 R은 0.5로 한다.
2. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
3. 적용 TERMINAL: ST730467, 468, 469


NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.5 RADIUS.
2. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE TERMINAL: ST730467, 468, 469


GENERAL TOLERANCE (HOUSING)

10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1

USED ON

RELAY & HS'G ASS'Y
SCALE 2:1

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG670928	RELAY 5F HOUSING	PA66	BLACK
②	MG631317	RELAY 5P R/H	PBT	NATURAL



					MATERIAL	SEE TABLE	 KET KOREA ELECTRIC TERMINAL CO., LTD.						
					FINISH	SEE TABLE							
					WIRE RANGE								
					INSULATION								
							CLASS						
	시원방(000000) 전자 수형 RELAY LOCKING (P.S. 200)				KYM		'05.04.25	TYPE					
LTR	REVISION RECORD				DR	CHK	APP	DATE	PREPARED AS NOTED	SEE TABLE	SCALE 2/1	PART NO.	MG640927
DR.	SUN '96.10.09				CHK.			10/09	10/10	PART NAME	RELAY 5F ASSY		
CHK.					APP			10/11	10/10				