






SECTION A-A



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.20	±0.25	±0.30	±30'	0.10	

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8		GREEN

NOTE

- 제품기능상 유해한 BURR, 변형 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL: ST730623, 624, 625
- 적용 HOUSING: MG51098
- SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지, 공급할 것.



ISSUE MARK

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG671099	.090 II W/P 4P REC. HOUSING	SEE TABLE	BLACK
2	MG671100	.090 II W/P 4P REC. FRONT HOLDER	SEE TABLE	NATURAL
3	P900705	.090 II W/P 4P INNER SEAL	SILICONE	RED

						MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
						FINISH	SEE TABLE	
						WIRE RANGE		CLASS .090 II SEALED
						INSULATION		TYPE 7283-7040
LTR	REVISION RECORD	DR	CHK	APP	DATE	TOLERANCE EXCEPT AS NOTED	SCALE 1/1	PART NO. MG641101
DR. WON. '97.03.07		CHK			7/13	PART NAME		.090 II W/P 4P REC. ASS'Y
CHK. CHOI. 7/14		APP.			7/14			