






SECTION A-A




SECTION B-B



GENERAL TOLERANCE (HOUSING)							USED ON
1MAX	5MAX	10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.10	±0.15	±0.20	±0.25	±0.30	±30'	0.10	

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG671526	1809 11P REC. HOUSING	PBT	NATURAL
2	MG671527	1809 11P REC. SPACER	PBT	YELLOW



NO.	MATERIAL	COLOR
0	P B T :	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8	GREEN	

NOTE

- 1.기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 2.적용 CONN'T: MG651525
적용 TERMINAL: ST740672, 673, 674(.090)
ST740631, 632, 633(.187)
- 3.CONNECTOR 삽입력 & 발거력: 12.0gf이하



ISSUE MARK

MATERIAL	SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	
INSULATION		TYPE	
LTR	REVISION RECORD	DR	SCALE
DR.	WON. '97.12.09	CHK.	2/1
CHK.	1/10	DATE	PART NO.
APP.	1/10	1/10	MG641528
PART NAME		1809 11P REC. HOUSING ASS'Y	