






GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	



주 기

1. 제품의 기능상 유해한 BURR, 변형 및 WELDLINE 등이 없을 것.
2. 적용 TERMINAL : ST740753.
3. 적용 HOUSING : MG651580
4. SIDE SPACER를 본 도면과 같이 1차 LOCK'G상태로 유지,공급할 것.

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST740753
3. APPLICABLE HOUSING : MG651580
4. R/HOLDER MUST BE KEEP AND SUPPLY FIRST LOCKING CONDITION AS THIS DRAWING.

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8		GREEN

NO.	PART NAME	PART NO.	MATERIAL	FINISH
1	050 10P REC. HS'G	MG671576	PBT	SEE COLOR TABLE
2	050 10P REC. SIDE SPACER HS'G	MG671557	PBT	NATURAL



ISSUE MARK

						MATERIAL	SEE TABLE	KET (ENGINEERED)	KOREA ELECTRIC TERMINAL CO., LTD.
						FINISH	SEE TABLE		
						WIRE RANGE		CLASS	
						INSULATION		TYPE	050
								SCALE	
							SEE TABLE	PART NO.	MG641577
						PART NAME			
						050 10P REC. HS'G ASS'Y			