


GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.	REMARKS
1	LIF 32P REC. HOUSING	MG671708	PBT	NATURAL	1	
2	LIF 32P REC. SPACER	MG671709	PBT	NATURAL	1	
3	LEVER	MG671710	PBT	BLACK	1	
4	SPRING	P900792	SUS	UNPLATE	1	



주 기

- 적용 HOUSING P/NO. : MG651711
- 적용 TERMINAL NO. : (040III) : ST740771-3 (CAVS 0.3~CAVS0.5)
 (090II) : ST740672-3 { AVS (CAVS) 0.3~0.5 }
 ST740673-3 { AVS (CAVS) 0.85~1.25 }
 ST740674-3 { AVSS 2.0 }
- SPACER가 HOUSING으로부터 이탈 되는것을 확인한다.
- * 표시 치수의 CENTER는 37.50 의 CENTER로 한다.



ISSUE MARK

				MATERIAL		SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.	
				FINISH		SEE TABLE		
				WIRE RANGE		CLASS		YAZAKI
				INSULATION		TYPE		7282-5667
LTR	REVISION RECORD	DR	CHK	APP.	DATE	ISSUE MARK	PART NO.	
DR.	MOOK 990302	CHK			9.14	SCALE	MG641707	
CHK.		APP.			9.15	PART NAME	LIF 32P REC. ASSY	