


GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	MG651050
±0.2	±0.25	±0.3	±30'	0.1	



주 기

1. 제품기능상 유해한 FLASH, 변형 및 WELDLINE등이 없을것.
2. 적용 TERMINAL : ST740672, 673, 674(.090 II TYPE : 8EA)
3. 적용 HOUSING : MG651050 (090II 8P PLUG HS'G ASS'Y)
4. SPACER는 1차 도면과 같이 1차 LOCK'G상태로 유지, 공급할 것.

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST740672, 673, 674 (.090 II TYPE : 8EA)
3. APPLICABLE HOUSING : MG651050 (090II 8P PLUG HS'G ASS'Y)
4. SPACER MUST BE KEEP AND SUPPLY FIRST LOCKING CONDITION AS THIS DRAWING.



NO.	PART NO.	PART NAME	MATERIAL	COLOR
1	MG671753	DOOR 8P REC. HOUSING	PBT	NATURAL
2	MG671052	.090II 8P REC. SPACER		NATURAL

MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.					
FINISH	SEE TABLE						
WIRE RANGE		CLASS SM CAR					
INSULATION		TYPE .090II					
LTR	REVISION RECORD	DR	CHK	APP.	DATE	SCALE	PART NO.
DR.	C. B. YUN '99.05.10	CHK			99.10.25	1/1	MG641763
CHK.		APP.	CHK	APP.	10/25		
PART NAME		DOOR 8P REC. HS'G ASS'Y					