



GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

GENERAL TOLERANCE (SILICONE RUBBER)					
50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT
±0.2	±0.3	±0.5	±0.75	±30'	0.1

NOTE

- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : (SSD) ST730622 / (090II) ST730689, ST730732, ST730733
APPLICABLE HOUSING : MG611764 / APPLICABLE REAR HOLDER : MG631766
- 6 HAZARDOUS SUBSTANCES IN PARTS(LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REULATION.

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG671765	SSD 16F HOUSING	SEE TABLE	SEE TABLE
②	R600072 (P900707)	SSD 16P I/S	SILICON	ORANGE

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL : (SSD) ST730622
(090II) ST730689, ST730732, ST730733
적용 HOUSING : MG611764 / 적용 REAR HOLDER : MG631766
- 제품내 함유된 6대 유해물질(납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
						SEE TABLE	2/1	MG641767
DR.	MAN	'99.03.31	CHK.	KKJ JJH	'99.03.31			
CHK.	S.I.JANG	'99.03.31	APP.	CHOSH	'99.03.31			
						MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
						FINISH	SEE TABLE	
						WIRE RANGE	CLASS	SSD + .090II W/P
						INSULATION	TYPE	
						ISSUE MARK		
						APPROVED 2021-01-07 KOREA ELECTRIC TERMINAL CO., LTD. Korea Electric Terminal Co., LTD.		
						PART NAME		
						SSD 16F HOUSING ASSY		