

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG671879	1809 16P REC. HS'G (L)	PBT	NATURAL
2	MG671005	1809 16P REC. SPACER		NATURAL


GENERAL TOLERANCE (HOUSING)				USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT
±0.2	±0.25	±0.3	±30'	0.1

## 주 기

1. 재용가능성 유해한 BURR, 변형 및 WELDLINE 등이 없음.
2. 적용 TERMINAL: ST740631,632,633 (187 II TYPE : 4 EA)  
ST740672,673,674 (C.090 II TYPE : 12 EA)
3. 적용 HOUSING: MG6518B1
4. SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지,공급할것.

## NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL :  
ST740631,632,633 (187 II TYPE : 4EA)  
ST740672,673,674 (C.090 II TYPE : 12 EA)
3. APPLICABLE HOUSING : MG6518B1
4. SPACER MUST BE KEEP AND SUPPLY FIRST LOCKING CONDITION AS THIS DRAWING



ISSUE MARK

						MATERIAL	SEE TABLE
						FINISH	SEE TABLE
						WIRE RANGE	CLASS
						INSULATION	TYPE
LTN	REVISION RECORD	DR	CHK	APP.	DATE	SCALE	PART NO.
JNL	WK	CHKD	99.09.01		9/1	SCALE	MG641883
CHK	9/1	APP	9/4			PART NAME	1809 16P REC. HS'G ASS'Y (L)