



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG672265	.090 WP 2P REC. HS'G(HR)	PBT	BLACK
2	MG672266	.090 WP 2P REC. FRONT HOLDER(HR)	PBT	NATURAL
3	P901083	.090 WP 2P INNER SEAL(HR)	SILICONE	RED

주 기.

- 제품기능상 유해한 BURR, 변형 및 WELDLINE 등이 없어야 함.
- 적용 TERMINAL : ST730689, 732, 739
- 적용 WIRE SEAL : MG680274, 275, 1474

NOTE

- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : ST730689, 732, 739
- APPLICABLE WIRE SEAL : MG680274, 275, 1474

ISSUE MARK

				MATERIAL	SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE	
				WIRE RANGE	CLASS	
				INSULATION	TYPE	
LTR	REVISION RECORD	DR	CHK	APP	DATE	PART NO. MG642267 PART NAME 090 WP 2P REC. ASS'Y(HR)
DR	S.H. HEO 00.12.20	CHK	YH	YH	2/1	
CHK		APP				