





SECTION A-A



GENERAL TOLERANCE (HOUSING)								USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT		MG651038
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1		

③	P901264	090 II JOINT TAB 4WAY	BRASS	PRE-TIN
②	MG672195	090 II EARTH/JOINT 4P R/HOLDER	PBT	BROWN
①	MG672193	090 II JOINT 4P REC. HS'G(CLIP TYPE)	PBT	NATURAL
NO.	PART NO.	PART NAME	MATERIAL	FINISH



주 기

1. 지시하지 않은 반경 R은 0.5로 한다.
2. 기동상 유해한 BURR 및 WELDLINE 등이 없을 것.
3. 적용 CONNECTOR : MG651038

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADII TO BE 0.5 RADIUS.
2. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE CONNECTOR : MG651038



ISSUE MARK

						MATERIAL	SEE TABLE	 KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH	SEE TABLE		
						WIRE RANGE		CLASS	.090 II
						INSULATION		TYPE	
						SEE TABLE		PART NO.	MG642349
						SCALE	2/1	090 II JOINT 4P REC. ASS'Y (CLIP TYPE)	
						PART NAME			