



GENERAL TOLERANCE (HOUSING)

10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	USED ON
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

- 지시없는 R는 전부0.3으로 한다.
- 기능상 유해한 BURR,변형등이 없을것.
- 적용 부품 : TERMINAL-ST740926/ST740927

R/HOLDER-MG632600

NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
- MUST BE FREE OF BURR,WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE PART : TERMINAL-ST740926/ST740927
R/HOLDER-MG632600

NO.	PART NAME	PART NO.	MATERIAL	REMARK
①	RK 2P REC' HS'G(RK02MGY)	MG672596	PBT	BROWN
②	RK 2P I/SEAL	P901424	SILICONE	RED

ISSUE MARK

				MATERIAL	SEE TABLE	 KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE	
				WIRE RANGE		CLASS 91RK (040 WP)
				INSULATION		TYPE 7282-7770-40
LTR	REVISION RECORD	DR	CHK	APP.	DATE	PART NO. MG642597
DR.	KYM 04.04.21	CHK.				
CHK.	04.26	APP.				
PART NAME						RK 2P REC' ASS'Y(RK02MGY)