



GENERAL TOLERANCE (HOUSING)

10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	USED ON
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 지시없는 R는 전부0.3으로 한다.
2. 기능상 유해한 BURR,변형등이 없을것.
3. 적용 부품 : TERMINAL - ST740926/ST740927
R/HOLDER-MG632606
4. 적용 HOUSING - MG612603

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
2. MUST BE FREE OF BURR,WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE PART : TERMINAL-ST740926/ST740927
R/HOLDER-MG632606
4. COMPARE HOUSING-MG612603



ISSUE MARK

NO.	PART NAME	PART NO.	MATERIAL	REMARK
①	RK 3P REC' HS'G(RK03MBR)	MG672601	PBT	BROWN
②	RK 3P I/SEAL	P901426	SILICONE	RED

						MATERIAL	SEE TABLE	 KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH	SEE TABLE		
						WIRE RANGE			
						INSULATION			
								CLASS	91RK (040 WP)
								TYPE	7282-7771-80
LTR	REVISION RECORD		DR	CHK	APP	DATE	SCALE		PART NO
							2/1		
DR.	KYM 04.04.21		CHK				SEE TABLE		MG642602
CHK.	46 04.26		APP	46	04.26	PART NAME			
						RK 3P REC' ASS'Y(RK03MBR)			