



SECTION A-A

GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

NOTE

1. 지시없는 R는 전부0.3으로 한다.

2. 기능상 유해한 BURR,변형등이 없을것.

3. 적용 부품

△ TM'L (312II WP) - ST730650,651,652,893,936

R/COVER - MG632935

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.

2. MUST BE FREE OF BURR,WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.

3. APPLICABLE PART

△ TM'L (312II WP) - ST730650,651,652,893,936

R/COVER - MG632935



NO	적용TERMINAL	ASSY/NO	PART/NO	PART/NAME	MATERIAL	FINISH
1	BRASS	MG642928-5	MG672929-5	312 II WP 2F HS'G	PBT	BLACK
2			P901715	312 II WP 2F IN/SEAL	SILICON	RED
3			MG672930	312 II WP 2F F/HOLDER	PBT	NATURAL
1	COPPER ALLOY	MG642928-5S	MG672929-5	312 II WP 2F HS'G	PBT	BLACK
2			P901715	312 II WP 2F IN/SEAL	SILICON	RED
3			MG672930-4	312 II WP 2F F/HOLDER	PBT	GRAY

				MATERIAL		SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH		SEE TABLE	
				WIRE RANGE			CLASS
				INSULATION			TYPE
				SEE TABLE		SCALE 1/1	PART NO. MG642928
				PART NAME		312 II WP 2F HS'G ASS'Y	

