


ISOMETRIC VIEW

- NOTE -

- TOLERANCE : ± 0.2 , ANGLE $\pm 3^\circ$
- CONPLANARITY : 0.1 MAX.
- PART CODE
H 6.5 x x x x - 5
PART NO.
PLUG ASS'Y
- Spec : ES91500-03
- Solder : Reflow Solder Only(Surface mount)



DIE NO.	
	APPROVED
	2021-01-07
	KOREA ELECTRIC TERMINAL CO., LTD. Korea Electric Te Terminal Co., Ltd

NO.	NAME	MATERIAL	FINISH	Q'TC
5	RECEP 40P COVER	Polyamide	UL94-V0, BLACK	1
4	METAL FITTING	Copper Alloy	Ni 1.3~3.0um + Sn 2.5um Min	2
3	RECEP POWER TM'L H6.8	Copper Alloy	Ni 1.3~3.0um + Au 0.1um Min(Contact) & Sn	4
2	RECEP SIGNAL TM'L H6.8	Copper Alloy	Ni 1.3~3.0um + Au 0.1um Min(Contact) & Au	40
1	RECEP 40P HS'G H6.8	Polyamide	UL94-V0, BLACK	1
		MATERIAL		
		FINISH		
		WIRE RANGE		CLASS Board to Board
		INSULATION		TYPE FLOATING P=0.5mm
LTR	REVISION RECORD	DR. CHK. APP. DATE	TOLERANCE EXCEPT AS NOTED	SCALE PART NO.
DR.	K.U.H 16.11.09	CHK. P.J.M 16.11.09	± 0.1	4:1 MG646083-5
CHK.		APP. K.H.C 16.11.09	PART NAME	
				0.5 FLOATING B TO B RECEPTACLE 40P ASS'Y H6.8 1/1

"6 hazardous substances in parts (Lead, Mercury, Cadmium, Hexavalent Chromium, PBBs, PBDEs) shall not exceed the maximum permissible concentration prescribed under EU ELV Directive & RoHS Regulation."