



GENERAL TOLERANCE (HOUSING)										USED ON
10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

주 기
 1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것,
 2. 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs) 은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서 는 안된다,
 3. 적용 TERMINAL(C025) ; ST741360, ST741361
 적용 TERMINAL(C060) ; ST741362, ST741363, ST741364
 적용 TERMINAL(I10) ; ST741285, ST741286, ST741287, ST741373
 적용 TERMINAL(ROSENBERGER FAKRA) ;
 59S100-1M4A4, 59S100-102A4 (2세대)
 59S16A-1M4T4, 59S16A-102T4 (3세대)

NOTE
 1. MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
 2. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.
 3. APPLICABLE TERMINAL(C025) ; ST741360, ST741361
 APPLICABLE TERMINAL(C060) ; ST741362, ST741363, ST741364
 APPLICABLE TERMINAL(I10) ; ST741285, ST741286, ST741287, ST741373
 APPLICABLE TERMINAL(ROSENBERGER FAKRA) ;
 59S100-1M4A4, 59S100-102A4 (2th Generation)
 59S16A-1M4T4, 59S16A-102T4 (3th Generation)

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
11		ORANGE
2		BLUE
22		JADE
3		YELLOW
4		GRAY
41		LIGHT GRAY
42		DARK GRAY
5		BLACK
61	LIGHT GREEN	
62	DARK GREEN	
7	BROWN	
9	MAGENTA	

NO	PART NO.	PART NAME	MATERIAL	FINISH	Q'TY
1	MG677490	025060110 22M HOUSING RSB(FAKRA)	PBT	SEE TABLE	1
2	MG677491	025060110 22M SPACER RSB(FAKRA)	PBT	NATURAL	1



ISSUE MARK

MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE	
WIRE RANGE		CLASS C025 / C060 / I10 / RSB FAKRA
INSULATION		TYPE NON WP
LTR REVISION RECORD DR, LJJ 2019, 05, 14 CHK, AJH 2019, 05, 14	DATE 20, 03, 18 DR, LJJ 2019, 05, 14 APP, CMS 2019, 05, 14	TOLERANCE SEE TABLE SCALE 1/1 PART_NO. MG646325 PART_NAME 025060110 22M ASSY RSB (FAKRA)