






GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.20	±0.25	±0.30	±30'	0.10	



NOTE

1. 제품 기능상 유해한 BURR 및 WELDING등이 없을것.
2. 적용 TERMINAL : ST730675 , 676 , 677
3. 적용 HOUSING : MG641071
4. SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지. 공급할것.

NO	PART NO	PART NAME	MATERIAL	FINISH
①	MG671066	090 II 15P PLUG HS'G	PBT	NATURAL
②	MG671067	090 II 15P PLUG HS'G SPACER	PBT	NATURAL



ISSUE MARK

		MATERIAL		SEE TABLE		
		FINISH		SEE TABLE		
		WIRE RANGE			CLASS	.090 II
		INSULATION			TYPE	
△ 사번: 990094호기 수평 LTR REVISION RECORD DR JANG 98.09.22 CHK. <i>CHAM</i> APP. <i>CHAM</i> 3.30	WOKI DR CHK. <i>CHAM</i> APP. <i>CHAM</i> 3.30	99.06.23 DATE 3.30 SCALE 1/1	99.06.23 DATE 3.30 SCALE 1/1	PART NO MG651068	PART NAME .090 II 15P PLUG HOUSING ASSEMBLY	