





GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	



주 기

1. 제품기능상 유해한 FLASH, 변형 및 WELDLINE 등이 없을 것.
2. 적용 TERMINAL : ST730751
3. 적용 HOUSING : MG641572
4. R/HOLDER는 본 도면과 같이 1차 LOCK'G 상태로 유지, 공급할 것.

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST730751
3. APPLICABLE HOUSING : MG641572
4. R/HOLDER MUST BE KEEP AND SUPPLY FIRST LOCKING CONDITION AS THIS DRAWING.

NO.	PART NO.	PART NAME	MATERIAL	COLOR
1	MG671573	050 18P PLUG HS'G	PBT	NATURAL
2	MG671574	050 18P PLUG R/HOLDER		NATURAL



ISSUE MARK

				MATERIAL SEE TABLE		 KOREA ELECTRIC TERMINAL CO., LTD.	
				FINISH SEE TABLE			
				WIRE RANGE		CLASS	
				INSULATION		TYPE 050	
				SEE TABLE		PART NO. MG651575	
				SCALE 2/1			
				PART NAME			

	사별판권(S0404B)가 도면 재작성	KDJ		04.11.15
	교차 및 형상 변경 05/08/08작성	KDJ		04.06.18

LTR	REVISION RECORD	DR	CHK	APP	DATE	REVISION AS NOTED	SCALE	PART NO.
DR	WK CHOI '99.05.12	CHK	W/S	5/13	PART NAME	050 18P	PLUG HS'G ASS'Y	
CHK		APP		5/13				