



SECT. A-A

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5	W/GREEN	BLACK
6		W/GREEN
7		BROWN
8		GREEN

NO.	PART NAME	PART NO.	MATERIAL	FINISH
1	050 10P PLUG HS'G	MG671578	PBT	SEE COLOR TABLE
2	050 10P PLUG SIDE SPACER HS'G	MG671579	PBT	NATURAL

GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

주 기

1. 제품의 기능상 유해한 BURR, 변형 및 WELDLINE 등이 없을 것.
2. 적용 TERMINAL : ST730751
3. 적용 HOUSING : MG641732, MG641577
4. SIDE SAPCER를 본 도면과 같이 1차 LOCK'G 상태로 유지,공급할 것.

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST730751
3. APPLICABLE HOUSING : MG641732, MG641577
4. R/HOLDER MUST BE KEEP AND SUPPLY FIRST LOCKING CONDITION AS THIS DRAWING.



ISSUE MARK

				MATERIAL		SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH		SEE TABLE	
				WIRE RANGE			CLASS
				INSULATION			TYPE 050
LTR	REVISION RECORD	DR	CHK	APP.	DATE	THROUGH HOLE	PART NO.
DR. W.K. CHOI	98.08.31	CHK	9/9			SEE TABLE	MG651580
CHK		APP.	9/5			PART NAME	050 10P PLUG HS'G ASS'Y